

Features VS Benefits


- * Mechanical compatibility with direct mounting of the LED modules to the Modular vacuum phase-transition LED Heat Sinks (Passive) thermal performance matching the lumen packages.
- * Modular design with mounting holes foreseen for direct mounting of a wide range of LED modules and COB's.
- * For Highbay designs from 12000 to 22000 lumen.
- * Thermal resistance range Rth 0.26°C/W.
- * Diameter 265mm standard height 130mm Other heights on request.
- * 2 standard colors clear anodized black anodized.
- * Design for Bridgelux, Citizen, Cree, Seoul, LG Innotek, Tridonic, Lumileds, Lustrous.....

Unique Advantages

- * Integration of heat super conduction and heat disspation. Reduce heat conduct resistance of heatsink to ZERO;
- * Low heat conduct temperaure difference, equivalent heatconductive ability 20 times better than copper;
- * More than 30% reduce of volume and weight than normal heatsinks;
- * Compared to normal extrusion heatsinks, Mingfa Tech's our vacuum phase-transition heatsinks can adapt higher power for the same size; Compared to normal extrusion heatsinks, Mingfa Tech's vacuum phase-transition LED heatsinks are much smaller volume
- * and lighter weight for the same power;
- * All aluminium, cost effective;

Mounting Options and Drawings & Dimensions

Example: HibayLED-265130-B-2



1 Anodising Color

B-Black C-Clear Mentioned models are an extraction of full product range.For specific mechanical adaptations please contact MingfaTech.


Z-Custom - MingfaTech reserves the right to change products or specifications without prior notice.


Notes:

Mounting Options - see graphics for details Combinations available

Ex.order code - 12

means option 1 and 2 combined







































The thermal data table







Tel:+86-769-39023131 E-fax:+86-(020)28819702 ext:22122 Email:sales@mingfatech.com Http://www.heatsinkled.com Http://www.mingfatech.com

