

Digital Multimeter ST33D

Introduction

- Auto range
- 3 1/2 LCD display with back light
- Data hold
- Low battery indication
- Auto power off
- Over load protection
- Safety Class:IEC61010,CAT II 600V
- Operation Temperature & Humidity:0-40°C(32-104°F) & <80%RH
- Storage Temperature & Humidity:-10 - 50°C(14-122°F)&<70%RH

Specification

	Range	Accuracy
DC Voltage	200mV/2V/20V/200V	±(0.5%rdg+2dgt)
	600V	±(0.8%rdg+2dgt)
AC Voltage	2V/20V/200V	±(0.9%rdg+3dgt)
	600V	±(1.2%rdg+3dgt)
DC Current	200µA/2000µA/20mA/200mA/10A	±(1.5%rdg+3dgt)
AC Current	200µA/2000µA/20mA/200mA/10A	±(1.5%rdg+4dgt)
Resistance	200Ω/2kΩ/20kΩ	±(0.8%rdg+2dgt)
	200kΩ/2MΩ/20MΩ	±(1.0%rdg+2dgt)
Frequency	200kHz	±(1.5%rdg+5dgt)
Features		
Display	2000 counts	
Diode Check	√	
Continuity	√	
Auto Range	√	
Data Hold	√	
Low Battery Indication	√	
Auto Power Off	√	
Back Light	√	
Over Load Protection	√	
General Information		
Power Supply	1*9V Battery (6F22)	
Dimension	138x68x30mm	
Weight	175g	
Packing	User Manual / Test Lead	