

Digital Multimeter ST72

Introduction

-Safety Class:IEC61010,CAT II 600V

-Operation Temperature & Humidity:0-40°C(32-104°F)&45%-80%

-Storage Temperature & Humidity:-20-60°C(-4-140°C)&45%-80%

Specification

	Range	Accuracy
DC Voltage	200mV/2V/20V/200V	$\pm(0.5\%rdg+2dgt)$
	600V	$\pm(0.8\%rdg+2dgt)$
AC Voltage (50Hz-400Hz)	2V/20V/200V	$\pm(1\%rdg+3dgt)$
	600V	$\pm(1.2\%rdg+3dgt)$
DC Current	200 μ A/2000 μ A/20mA/200mA	$\pm(1.5\%rdg+3dgt)$
	10A	$\pm(2\%rdg+5dgt)$
AC Current	200 μ A/2000 μ A/20mA/200mA	$\pm(1.5\%rdg+4dgt)$
	10A	$\pm(2.5\%rdg+4dgt)$
Resistance	200 Ω /2k Ω /20k Ω /200k Ω /2M Ω	$\pm(0.8\%rdg+2dgt)$
	20M Ω	$\pm(1.0\%rdg+2dgt)$
Battery Test	1.5V/6V/9V/12V	
Features		
Display	2000 counts	
Diode Check	√	
Continuity	√	
NVC Test	√	
Auto Range	√	
Data Hold	√	
Low Battery Indication	√	
Auto Power Off	√	
Flashlight	√	
Back Light	√	
Over Load Protection	√	
General Information		
Power Supply	3*1.5V AAA Battery	
Dimension	147x71x45mm	
Weight	190g	
Packing	User Manual / Test Lead	