


## Window Tint Meter



Model: WTM-1000 WTM-1100

### Applications

Applicable to measure the transmittance of all kinds of transparent, translucent samples with parallel plane (such as automobile manufacturing, aerospace, glass products, plastic sheet, sheet, etc). Also can be used to determine the turbidity or clarity of liquid sample (water, drinks and so on).

### Features

- \* This Meter is a hand held device that measures the amount of light that passes through a window.
- \* Technology is designed in accordance with GB 2410-80, ASTM D1033-61, JIS k7105-81 and other standards.
- \* Digital display, wide range, high resolution.
- \* One key calibration, easy to use.
- \* Solid structure, small volume, light weight, easy to carry.
- \* Use USB data output to connect with PC.
- \* Provide Bluetooth data output choice.

### Specifications

Model	WTM-1100	WTM-1000
Display	LCD	
Range	0~100%	
Resolution	0.1	
Accuracy	$\pm 2\%$	
Sample Thickness	$\leq 18\text{mm} / 0.7\text{inch}$	$\leq 10\text{mm} / 0.4\text{inch}$
Light Source	LED	
Operating Conditions	Temperature: 0~50°C Humidity: < 90%	
Power Supply	4x1.5V AAA (UM-4) Battery	

Model		WTM-1100	WTM-1000
Size	Main Unit	126x65x27 mm	126x65x27 mm
	Sensor	125x38x38 mm	—
Weight		100 g (Not Including Batteries)	
Standard		Main Unit	
Accessories		Carrying Case (B04)	
		Operation Manual	
Optional		USB Data Cable with Software	
Accessories		Bluetooth Data Adapter with Software	

