

## Mini AC/DC Clamp Meter ST3108A

### DC Voltage

Range	Resolution	Accuracy
600mV	0.1mV	±(0.8% +3 digits)
6V	0.001V	
60V	0.01V	
600V	0.1V	±(1.0% +5 digits)

### AC Voltage

Range	Resolution	Accuracy
6V	0.001V	±(1.2% + 5digits)
60V	0.01V	
600V	0.1V	±(1.5% + 10digits)
200-600V (V.F.C)	0.1V/1V	±(4% + 10digits)

### AC Current

Range	Resolution	Accuracy
60A	0.01A	±(3% + 6digits)
600A	0.1A	

### DC Current

Range	Resolution	Accuracy
60A	0.01A	±(3% + 6digits)
600A	0.1A	

### Resistance

Range	Resolution	Accuracy
600Ω	0.1Ω	±(1.2%+2 digits)
6kΩ	0.001kΩ	
60kΩ	0.01kΩ	
600kΩ	0.1kΩ	
6MΩ	0.001MΩ	
60MΩ	0.1MΩ	±(2.0 %+ 5digits)

### Capacitance

Range	Resolution	Accuracy
60nF	0.01nF	±(4.0% +3 digits)
600nF	0.1nF	
6μF	0.001μF	
60μF	0.01μF	
600μF	0.1μF	
6000μF	1μF	
60000μF	10μF	



### Temperature

Range	Resolution	Accuracy
-20~500°C/-4-932°F)	0.1°C/°F	±2%

### Features

Display	6000 Counts
True RMS	√
NCV (Non Contact AC Voltage Detector)	√
LOWz	√
Data hold	√
Work light	√
Diode test	√
Max/Min Value hold	√
Continuity Buzzer	√
Auto Off	√
Low battery indication	√
Back light	√

### General Information

Power supply	1.5V(AAA)x2 Batteries
Weight	Approx 195g
Size	191mmx70mmx37mm
Jaw Size	Ø25mm
Safety Rating	CE CAT.III600V RoHS

### Packing :

- Test Leads
- Operation Manual
- Clamp Meter
- Temperature Probe