

Gloss Meter GM-60G

Application :

This very handy smart tool used widely in production, at the lab, or with the customer related to the following industries :

- Floor maintenance
- Surface cleaning quality control
- Stone and tile gloss measurement
- Quality control of paint and ink
- Polished metal surface ,measurement (chrome plating)
- Inspection of paint protection and waxing
- Auto-body paint inspection
- Surface inspection of plastic moldings
- Evaluation of detergents and washers
- Checking masonry and washers
- Checking building exteriors
- Furniture Manufacture
- Yacht Manufacture



Features:

The 60° angle is universal for all applications

Auto Power off Function

With high accuracy (± 1 gloss points)

Low power consumption: works 40 hours and measures approximately 10000 data continuously

Highly damp proof , assures the instrument works under any terrible condition.

Low drift white light source of lumen : 6.0-7.01m to guarantee long term stability

The rock solid base and the extremely stable mounted optical components assures measurements to be accurate under all circumstances and conditions.

Covered by 2 years warranty

Specifications:

Measuring Range: 0-199.9GU (GLOSS UNIT)

Optical measurement angle :60 °

Stability: $\leq \pm 0.4$ Gs/30Min

Indication Error: $\leq \pm 1$ GU

Power Supply: 2*1.5V, AAA battery

Light Spot Size: 10*20mm

Size of the Measuring hole: 20*40mm

Environment Condition: Temperature: 0-40°C

Relative Humidity: < 85%RH

Product Size: 145*28*70mm

Product weight: 240g

Package Size: 250 * 180* 750 mm

Package weight: 1000g

Package: Aluminum Carrying Case

