

KEUNDO

SUPRAQ - 3200-TX6

Grand Format Direct Sublimation Printer



KEUNDO Sublimation Ink
C M Y K Lc Lm




AIR DEGASSING UNITS
It removes micro bubbles in ink while transferring ink to main ink tank.




AUTO CLEANING SYSTEM
Clean head and head plate automatically by built program.




PINCH ROLL
It gives stable media feeding with equal pressure on media




DANCER BAR
It can maintain constant media tension to secure stable feeding.




FRONT DRYER
Applied FIN to the outside of dryer for wide dry after print. It could dry textile material(s) perfectly on any mode of pass(es).



AIR-SHAFT ROLL
Adjust Air-shaft roll to install media more conveniently.



VERSATILITY
Depending on the purpose of printing by fabric(s) or transfer paper, the printing platform is changeable between vacuum plate for paper and waste ink slot for fabric.



GUTTER JETTING SYSTEM
Makes nozzle spit to prevent head from nozzle clog.

SPECIFICATIONS

HEAD	SG-1024 Robust and repairable construction, 12picoliter nominal drop size
INKS	Water based Disperse Sublimation, 6 colors (C, M, Y, K, Lc, Lm)
INK CAPACITY	Main ink pail or Main ink Cartridge and Reservoir tank : 200ml
MATERIAL TYPE	Pre-coated Dye-Sublimation Polyester, Mesh polyester, Transfer paper(In-Direct) and etc..
MATERIAL SIZE	Width : 3.2Meter , Roll Diameter : 400mm
PRINTING METHOD	Roll to Roll
PRINT SPEED	Production mode : 85sqm/h Quality mode : 57sqm/h High quality mode : 42sqm/h
RESOLUTION	400 dpi
MAIN PROCESSOR & S/W	Intel I3 & Windows OS
RIP	CMS (Options Caldera)
POWER	AC380V, 3 Phase, 25KW
DIMENSION & WEIGHT	5,955(w) x 1290(d) x 2085(h)(Unit : mm) / 1,550Kg , 3,417lb(Pound)



SCG DIGITAL AMERICA INC.

Address: 13300 Brooks Dr. #D Baldwin Park, CA 91706

Phone: (626)223-4492 / (626)552-5075

Website: www.scg-america.com Email: marketing@scg-america.com