

Portable Pressure Steam Sterilizer

Characteristics:

1. Fully stainless steel structure.
2. Double scale indication pressure gauge.
3. Electric heated.
4. Easy to operate, safe and reliable.



Main Technical Parameters:

Model	Capacity	Working pressure	Working temperature	Max. safety pressure	Heat average	Power	Packing size	G.W/N.W
FSF-18LD	18L Φ280×260mm	0.14- 0.16Mpa	126°C	0.165Mpa	≤±0.1°C	2KW/ AC220V.50Hz	410×410×520mm	18kg/16kg
FSF-24LD	24L Φ280×390mm						410×410×630mm	19kg/17kg

Table Top Steam Sterilizer

Characteristics:

1. Sterilizing course: Automatic sterilization controlled by computer, easy to operate..
2. Maximum temperature: 134°C, suitable for 4-6 minutes flash sterilizing.
3. Safe protection of water lacking.
4. With over-temperature, over-pressure auto-protect device.
5. After sterilization it will automatically cut the power and then alarm.
6. Fully stainless steel structure .



Main Technical Parameters:

Model	FSF-T24J
Capacity	24L (Φ270×410)mm
Max. working temperature	134°C
Max. working pressure	0.22Mpa
Temp. range	105°C ~134°C
Timer	0~60 mins
Heat average	≤±1°C
Power	1.5KW/AC220V.50Hz
Exterior size	560×350×500mm
Packing size	620×410×570mm