

- This kind of tape can be laminated with release film
- This kind of tape can be supplied as customized discs

Technical Data

Oct. 2014

Product Description

Creative™ Uniontape™ MYL 5035gl-3 is a kind of translucent, polyester film-backed silicone adhesive tape.

Product Construction



- Polyester film
- Silicone adhesive
- Release film



Specifications

ITEMS	UNIT	VALUE	TESTING METHODS	REMARKS
Color		Green	Visual test	
Backing Thickness	mm	0.050	ASTM D-3652	
Total Thickness	mm	0.085	ASTM D-3652	±0.005mm
Adhesion to Steel	N/25mm	10.5~13.5	ASTM D-3330	
Adhesion	g/25mm	≤15	ASTM D-3330	
Tensile Strength	N/25mm	≥150	ASTM D-3759	
Elongation at Break	%	≥100	ASTM D-3759	
Temperature Resistance	°C/30min	204		
Standard Roll Length	m	66		

Features

Moderate viscosity ,no residue ,high temperature resistance ,corrosion resistance,no damage to the capacitor.

Applications

MLCC process, electroplating protection.

Storage Conditions & Shelf life

Store under normal conditions of 73°F (23°C) and 20~80% R.H. in the original carton. To obtain best performance, the product should be used within 12 months from the date of manufacture.

Notes

All above-mentioned techniques are the average values obtained after our several testing by acknowledged and reliable testing methods. In order to ensure the correct selection and using of our products, please make a through understanding both of the purposes and conditions on usage in advance, or notify us as to provide you with further explanation and service.

Suzhou Creative Electronics Co., Ltd

Suzhou Plant

Add:No.209,Caofeng Road,Xukou Town,
Suzhou 215156, P.R.China

Suzhou Sales Office

Add:No.209,Caofeng Road,Xukou Town,
Suzhou 215156, P.R.China
Tel: 86-512-66930508
Fax: 86-512-68635760

Shanghai Creative Laminates Co., Ltd.

Shanghai Sales Office

Add:Room 2305, Building E, No.82 Caobao
Road, Shanghai 200235, P.R. China

Tel: 86-21-64836331, 64327879, 64327873

Fax: 86-21-64833821

www.uniontape.com

Email: sales@uniontape.com