


Technical Data
Dec.2008
Product Description

Fluoride release film is the kind of polyester film backed with fluoride release reagent, which is developed for the adhesives of silicone.

Product Construction

Specifications

Grades	Color	Release Force	Backing Thickness(mm)	Subsequent Adhesion Rate
FR7520	Colorless	10.0~20.0	0.075	
Remarks		g/25mm	±0.001mm	

Features

It provides very consistent and stable release force and has excellent chemical solvents resistance.

Applications

High performance label with silicone PSA as backing; Silicone/Acrylic double-sided tape;
 Silicone/silicone double-sided tape.

Storage Conditions & Shelf life

Store under normal conditions of 73°F (23°C) and 20~80% R.H. in the original carton. To obtain best performance, the product should be used within 12 months from the date of manufacture.

Notes

All above-mentioned techniques are the average values obtained after our several testing by acknowledged and reliable testing methods. In order to ensure the correct selection and using of our products, please make a through understanding both of the purposes and conditions on usage in advance, or notify us as to provide you with further explanation and service.

Suzhou Creative Electronics Co., Ltd
Suzhou Plant

Add:No.209,Caofeng Road,Xukou Town,
 Suzhou 215156, P.R.China

Suzhou Sales Office

Add:Rm 200,Sanyuan Building, No.1381 Ganjiang Rd.(W),
 Suzhou 215004, P.R.China
 Tel: 86-512-68665355
 Fax: 86-512-68629984

Shanghai Creative Laminates Co., Ltd.
Shanghai Sales Office

Add:Rm 2801 & 2803, Building F, No.86 Caobao
 Road, Shanghai 200235, P.R. China
 Tel: 86-21-64836331, 64327879, 64327873
 Fax: 86-21-64833821
 www.uniontape.com
 Email: sales@uniontape.com