

Magnetic Stirrer

○Magnetic mixing equipment with heating.

Characteristics:

- Heating power and stirring speed is stepless adjustable.
- With adjustable thermometer rack, stainless steel rods and the stir bar.
- SH-(C) series: Ceramic Plate



Main Technical Parameters:

Patent No. : ZL 2018 3 0095053.5

Model		SH-2A	SH-2B	SH-2	SH-3A	SH-3B	SH-3
		SH-2A (C)	SH-2B (C)	SH-2 (C)	SH-3A (C)	SH-3B (C)	SH-3 (C)
Function	Max. Volume (ml)	-	2000	2000	-	5000	5000
	Speed (r.p.m)	-	100~2000		-	100~2000	
	Working Time	Continuous					
	Minimum Revolution (r.p.m)	-	100	100	-	100	100
	Max.Temp. (°C)	380	-	380	380	-	380
Structure	Exterior	Cast aluminium, Surface spraying / Ceramic Coated					
	Plate Size(mm)	120 × 120			170 × 170		
	Driving Mode	-	Motor		-	Motor	
	Motor Power (W)	-	10		-	20	
	Heating Power(kW)	0.18	-	0.18	0.5	-	0.5
	Stir Bar	-	PTFE		-	PTFE	
Controller	Continuous Operation	Yes					
	Setting Mode	Scale					
	Speed Display Mode	-	Scale		-	Scale	
	Timer	No					
	Operation Function	No					
	Temp. Sensor	No					
Specification	Exterior Size (W*L*H)(mm)	200 × 120 × 90			265 × 185 × 190		
	Packing Size (W*L*H)(mm)	250 × 180 × 120			280 × 210 × 220		
	Plate Size (mm)	120 × 120			170 × 170		
	Plate Load	3KG			10KG		
	Power Supply (50/60Hz)	110V or 220V					
	Current Rating						
	NW/GW (kg)	1.9/3	1.9/3	1.9/3	2.2/3.4	2.2/3.4	2.2/3.4