

Quotation/Speciction of HD H.264 DVB-C Catcast Technology Co., Ltd. (Chengdu)

Customer Info.:					
Company:		Atten:		E-mail:	
Tel:		Fax:		Web:	
Quotation Info.:					
Model No.:	DVB-C	Product Description:	HD DVB-C H.264 set-top box (HP8203)	Price: (FOB SHENZHEN)	
Function and Standard	<input checked="" type="checkbox"/> HDMI <input type="checkbox"/> CE <input type="checkbox"/> Time shift <input checked="" type="checkbox"/> CA <input type="checkbox"/> CI <input checked="" type="checkbox"/> LED display <input type="checkbox"/> RoHs <input type="checkbox"/> 3G <input checked="" type="checkbox"/> Wifi			Required Qty.	
MOQ:	3000 pcs		Lead Time:	30-35 days after receiving 30% deposit	
Payment Term:	30% deposit and 70% balance before the shipment				
Spare parts:	1% CBU		Warranty:	12 months	
Specification:		System and Memory:		Product Photo:	
<ul style="list-style-type: none"> ● DVB-C, compliane with EN 300 429 ● Support 16,32,64,64 and 256-QAM ● Video decoder: MPEG-4/H.264 HP@L4.1, MPEG-2 MP@HL ● Audio decoder: AAC/HE-AAC/AC3, DD+(Optional)/PCM ● HDMI 1.3 and full HD up to 1080P ● PAL&NTSC auto switch ● USB for PVR,time shift and Media playback ● Support Subtitle and VBI/OSD Teletext ● Auto scan and manual scan ● Support Favorites Group,Parental Lock ● USB and OTA update ● Support 7 days EPG,display present/next program ● Support ISO-7816 Smart Card Interface 		<ul style="list-style-type: none"> ● Main Processor: Montage CC6000-T ● Flash Memory: 8MB ● SDRAM:1GB 			
		Demodulator: <ul style="list-style-type: none"> ● Modulation mode: OFDM (Orthogonal Frequency Division Multiplexing) ● Demodulation: 16QAM , 32QAM, 64QAM, 128QAM, 256QAM, ● Guard interval: 1/4, 19/128, 1/8, 19/256, 1/16, 1/32, 1/128 ● FEC Code rates: 1/2, 3/5, 2/3, 3/4, 4/5, 5/ 			
Connetcor:		Tuner:		General Data:	
<ul style="list-style-type: none"> ● RF Input: 1 x F, Female ● RF Output: 1 x F, Male ● Digital Video Output: 1 x HDMI ● Analog Output: CVBS/L/R YPbPr ● USB: 1 x USB2.0 for upgrading, multi-media play, PVR and Timeshifting ● Digital Audio Output: 1 x Coaxial ● CA slot 		<ul style="list-style-type: none"> ● High sensitive and reliable silicon tuner: M88TC3800 ● Input Frequency Range:48MH~1GHz ● IF Bandwidth: 6, 7 or 8MHz ● Input Signal Level : -85dBm ~ -20dBm ● RF Input Connector: D-type connector (RF IN) ● Input impedance: 75Ω 		<ul style="list-style-type: none"> ● Input Voltage: DC II ● Power Consumptio ● Operation Tempera 0~40℃, Humidity<95 ● Operating tempera 40℃ 	
Standard Packing Accessories		Packing Size:	mm	Loading Quantity (pc	
Item	Qty.	Product size:	160 x 120 x 30	20" GP	40" GP
Remoete control	1 pc	Gift Box:	200 x 60 x 120	11,110	22,220
User Manual	1 pc	Carton Box:	340 x300x 240	Qty/Ctn	10
AC cable	1 pc				
ADAPTOR	1 pc				
Battery	1 pair				
Additional Accessories			Remark	More	
Item	Qty.	Cost up			
HDMI cable		USD			

