


Notes:
 1. Raceway of inner & outer ring induction hardened, hardness: 55~62HRC
 Depth ≥ 3.5mm
 2. Inner & outer ring quenched & tempered, hardness: 207~262HB

Gear Data				Design		Check		Model				Weight	
Module	m	6	Gear heat treatment requirements		Date	Approve		113.25.630				100kg	
Teeth no	z	83	HRC		Qty	Size	Axial clearance	0.00~0.02				Scale	
Teeth pressure angle	α	20°	Precision(GB10095-88)	10	Inner ring mounting hole	24	Φ18	Radial clearance	0.00~0.02				
Modification coefficients	x	+0.5			Outer ring mounting hole	24	Φ18	machine tolerances without notes					
Reduction coefficients	km	1.2			Oil hole	4	M10×1	≤200	≤500	≤710	≤1120		
Pitch diameter	d	498						±0.30	±0.40	±0.50	±0.65		
								≤1600	≤2000	≤2500	≤3150		
								±0.80	±0.95	±1.10	±1.35		
								≤4000	≤5000				
								±1.65	±2.0				
								Technical processing standards without notes according to ...JB/T2300-2011					
					T:Pulg location S:Soft zone Y:Oil hole Z:Lifting hole			XUZHOU WANDA SLEWING BEARING CO.,LTD  Fax: +86 516 83309366 Fax: +86 516 83915766 http://www.slew-bearing.com					