

# Electric-heated Vertical Steam Sterilizer

(Fully automatic microcomputer)

## Characteristics:

1. Fully stainless steel structure.
2. Hand wheel type of quick-open door structure.
3. Door safety lock system.
4. Automatically controlled by computer.
5. Digital display of working status, touch of key.
6. Over temperature & over pressure auto-protection.
7. Steam-water inner circulation system: no steam discharge, and the environment for sterilizing will be clean and dry.
8. Self-inflating type seal.
9. Safe protection of water lacking.
10. The drying system is optional, which can be equipped according to the customers' request.
11. Automatically shut off with beep reminding after sterilization.
12. With two stainless steel sterilizing baskets.



## Main Technical Parameters:

Model	FSF-35HG	FSF-50HG	FSF-75HG	FSF-100HG
Capacity	35L (Φ318×450)mm	50L (Φ340×550)mm	75L (Φ400×600)mm	100L (Φ440×650)mm
Working pressure	0.22Mpa			
Working temperature	134°C			
Max.working pressure	0.23Mpa			
Heat average	≤±1°C			
Timer	0~99min or 0~99 hour 59 min			
Temp.range	0~134°C			
Power	2.5KW/AC220V.50Hz	3KW/AC220V.50Hz	4.5KW/AC220V.50Hz	
Exterior size	600×410×1030mm	650×410×1140mm	690×470×1140mm	730×510×1270mm
Packing size	730×500×1170mm	730×500×1290mm	760×550×1290mm	820×600×1380mm
G.W/N.W	96kg/77kg	102kg/83kg	120kg/98kg	135kg/110kg