

◆ Technical Data:

Model:EXM-E-8AC-R

RIEV/TECH



1.8 pcs extensions can be applied to the EXM or ELC-12-N CPU
 2.Connection cable length can be up to 3M(EXM-CB-B cable is required)

Technical Index

Power supply:	
Nominal voltage	AC110V-240V
Operating limits	AC85 - 265 V
The main frequency range	47-63Hz
Max. absorbed power	34mA (85V ac) ; 26mA (265V ac)
Isolation voltage	1780V AC
Protection against polarity inversions	Yes
Input parameters:	
Input No	4 (I1-I4)
Digital input	4 (I1-I4)
Analogue input	None
Input voltage	AC110-240V
Input signal0	AC0-40V; <0.03mA
Input signal1	AC79-240V; >0.06mA
Input Response Time	Delay time at 0 to 1: 120V AC : Typ. 50 ms 240V AC : Typ. 30 ms Delay time at 1 to 0: 120V AC : Typ. 90 ms 240V AC : Typ.100 ms
Maximum counting frequency	Typ. 4Hz
Sensor type	Contact or 3-wire PNP
Isolation between power supply and inputs	None
Isolation between inputs	None
Protection against polarity inversions	Yes
Output parameters:	
Output No.	4 (Q1-Q4)
Output type	Relay output
Continuous current	(Q1-Q2) Resistive load 3A/Inductive load 1A (Q3-Q4) Resistive load 10A/Inductive load 2A
Max. breaking voltage	AC 250 V DC 110 V
Max. Allowable Power Force	(Q3-Q4)1250VA 300W (Q1-Q2) 500VA 100W

Electrical durability Expectancy	10 ⁵ Operations at Rated Resistive Load
Mechanical life	10 ⁷ Operations at No Load condition
Response time	Operate Time : 15 mSec. Max. Release Time : 10 mSec. Max.
Built-in protections	Against short-circuits: None Against overvoltages and overloads: None
Switch frequency:	
Mechanism	10Hz
Resistor/light load	2Hz
Sensitive load	0.5Hz
Other parameters:	
Operation temp	-20°C-55°C
Storage temp	-40°C-70°C
Weight	Approx.250g

Installation Dimensions & Wiring Diagram

