

- This kind of tape can be laminated with release film
- This kind of tape can be supplied as customized discs

Technical Data

Feb.2012

Product Description

Creative™ Uniontape™ GL 1350P is a kind of glass cloth backed acrylic adhesive tape.

Product Construction



→ Glass cloth
→ Acrylic adhesive



Specifications

ITEMS	UNIT	VALUE	TESTING METHODS	REMARKS
Color		White	Visual test	
Backing Thickness	mm	0.130	ASTM D-3652	±0.002mm
Total Thickness	mm	0.180	ASTM D-3652	±0.005mm
Adhesion to Steel	N/25mm	7.0~11.0	ASTM D-3330	
Unwinding Force	g/25mm	—		
Dielectric Strength	KV	≥2.5		
Temperature Resistance	°C/30min	155		
Standard Roll Length	m	55		

Features

Single Glass Cloth Tapes have good performance in high temperature, insulation grade F.

Applications

GL series products are ideal for powder coating. Also have excellent performance in electrical insulation, wire wrapping, thermal insulation gaskets.

Storage Conditions & Shelf life

Store under normal conditions of 73°F (23°C) and 20~80% R.H. in the original carton. To obtain best performance, the product should be used within 12 months from the date of manufacture.

Notes

All above-mentioned techniques are the average values obtained after our several testing by acknowledged and reliable testing methods. In order to ensure the correct selection and using of our products, please make a through understanding both of the purposes and conditions on usage in advance, or notify us as to provide you with further explanation and service.

Suzhou Creative Electronics Co., Ltd

Suzhou Plant

Add:No.209,Caofeng Road,Xukou Town,
Suzhou 215156, P.R.China

Suzhou Sales Office

Add:Rm 200,Sanyuan Building, No.1381 Ganjiang Rd.(W),
Suzhou 215004, P.R.China

Tel: 86-512-68665355

Fax: 86-512-68629984

Shanghai Creative Laminates Co., Ltd.

Shanghai Sales Office

Add:Rm 2801 & 2803, Building F, No.86 Caobao
Road, Shanghai 200235, P.R. China

Tel: 86-21-64836331, 64327879, 64327873

Fax: 86-21-64833821

www.uniontape.com

Email: sales@uniontape.com